# Self Contained Ice Machine up to 108 kg

# **EF 103 EASY FIT**



## Self Contained Ice Machine up to 108 kg

Item #:	
Project:	
Quantity:	



### **FEATURES**

- Electronically controlled operation, with self-diagnostic functions with external alarm lights providing operational information for early alert and fast diagnosis of operating issues.
- External Components constructed from corrosion-resistant stainless steel crafted for optimal aesthetic appeal through superior fit and finish.
- Ergonomically convenient, slanted & disappearing storage bin door.
- Front Access for Easier Maintenance.
- Front-in, front-out airflow allows for built-in installations.
- PWD Progressive Water Discharge: pumps excess residual water up to a distance of 15 meters.

	CONDENSING SYSTEM	INTERNAL BIN CAPACITY					
	Air cooled Water cooled	30 kg					
	REFRIGERANT GAS	OPERATING REQUIREMENTS					
%	R404A		Minimum	Maximum			
		Air temperature	10°C	43°C			
	VOLTAGE V/Hz/ph	Water temperature	5°C	38°C			
	230/50/1	Water pressure	1 bar (14 psi)	5 bar (70 psi)			
		Electrical voltage	-10%	+10%			



EF 103 EASY FIT Residual water content 25%

### Certifications:





















# **EF 103 EASY FIT**




# Self Contained Ice Machine up to 108 kg


Item #:
Project:
Quantity:







AIR FLOW



UNIT OF MEASUREMENT: mm

- 1. 13/16" WATER OUTLET
- 2. 3/4" GAS WATER INLET
- 3. 3/4" GAS WATER OUTLET WATER COOLED UNIT ONLY
- **4.** 3/4" GAS WATER INLET WATER COOLED UNIT ONLY
- 5. CORD SET

5 2 0
-------

UNIT DATA	
Size (W x D x H)	592 x 622 x 1078 mm
Net weight	68 ka

		Comp	ressor	Circuit	Max. Tuse size	
Version	Voltage	Btu/h	W	No.	Ømm²	Α
EF 103 AS	230/50/1	1535	450	3	1.5	10
EF 103 WS	230/50/1	1535	450	3	1.5	10

### SHIPPING DATA

**Carton (W x D x H)** 670 x 690 x 1180 mm

Weight 76 kg

			24 h ice production kg °C Amb. / °C Water			Energy consumption*		Water usage*	Instant power
Version	Condensation	Voltage	10°C/10°C	21°C/10°C	32°C/21°C	kWh/100 kg	kWh/24h	l/h	W
EF 103 AS	Air	230/50/1	105	102	80	11.2	10.0	3.3	470
EF 103 WS	Water	230/50/1	108	106	89	10.5	9.0	32.1	360

<sup>(\*)</sup> Data refer to 32°C Amb. / 21°C Water temperature conditions